



DEALER FACT SHEET

AntOn by Jungheinrich PTL 1.5

Lithium-ion Pallet Truck Load capacity 1,500 kg

AntOn by Jungheinrich PTL 1.5 A pallet truck for every task.

As a powerful entry-level model focused on functionality and ease of use, the AntOn by Jungheinrich PTL 1.5 meets the demands of modern logistics environments with maximum reliability. Whether in the warehouse, on the shop floor or aboard a truck — the PTL 1.5 flexibly adapts to a wide range of applications and delivers exactly what's expected.



Your Sales Arguments:

- ► Entry-level model with strong core functionality
 - Load capacity: 1,500 kg
 - Weight incl. battery: 135 kg
- State-of-the-art lithium-ion technology
 Maintenance-free, long-lasting, fast-charging
- ► Fast opportunity charging via external charger
- Various fork versions available
 Suitable for common transport tasks
- Custom configuration options
 - Stabilising wheels for added safety on uneven surfaces
 - Second battery slot for extended runtimes in full-shift operations
- Practical self-service support
 Fast spare parts availability and video instructions



Your Advantages as a Dealer:

- High sales potential in Class 3.1
- ► Advanced technology at an attractive entry price
- Reliable operation thanks to robust, durable design
- Reduced freight costs due to high container density 4 units per packaging unit (standard), 176 units per container



Demo units available from:

SEPTEMBER 2025



AntOn by Jungheinrich PTL 1.5 At a glance.

Key Technical Data. (Excerpts) (Full technical specifications available on request or in the datasheet)

Load capacity	1,500 kg
Weight (incl. battery)	approx. 135 kg
Dimensions (L x W x H)	approx. 1,550 x 560 x 1,230 mm
Battery technology	Lithium-ion, 24 V/20 Ah
Total capacity	480–960 Wh
Charging options	Second battery slot
Charging time (per battery)	approx. 4 hours
Charger	External charger 230 V / 5 A
Maximum Operating time	2 hours
Application	Suitable for indoor use





riangle Configuration Examples.

(Full technical specifications available on request or in the datasheet)

Configuration 1 (standard)	► Lithium-lon battery, 24 V/20 Ah ► External charger
Configuration 2	Additional: ► Stabilising wheels for added safety on uneven ground
Optional	► Second battery slot for extended runtime during full-shift operations

Get in touch now and secure your market position early!

Your contact:

Max Mustermann

Sales Industrial Trucks Phone +49 123 456 789 max.mustermann@firma.de

